


C	→ 简介		→ 外形结构	
	(		× × : 17.8mm×110mm×117mm	
			NPDL- C102 X X 011	
			2 1	
				
			→ 安装	
		○ DIN IEC 60715 35mm		
		○		
		A		
		DIN		

→ 技术参数	
供电电源: 18V DC~32V DC (24V DC)	
输入(1 2):	
0~1A; 0~2.5A; 0~5A; 0~10A	
输出(7 8 9):	
4mA~20mA	
0(4)mA~20mA; 0mA~10mA	
1~5V; 0~5V; 0~10V	
负载能力:	
$R_L \leq [(U-3)/0.024]\Omega$; U	
0(4)mA~20mA: $\leq 550\Omega$; 0mA~10mA: $\leq 1.1k\Omega$	
0(1)V~5V: $\geq 1M\Omega$; 0V~10V: $\geq 2M\Omega$	
传输精度: 0.2%F.S. (0~120%)	
输出纹波: $< 16mV_{rms}$ (250 Ω)	
温度漂移: 0.01%F.S./ $^{\circ}C$	
频率响应: 40Hz~1kHz	
响应时间: $< 330ms$	
过载能力: 2	
电磁兼容: EMC IEC 61326-3-1	
介电强度 (漏电流1mA 测试时间1分钟):	
$\geq 1500VAC$ (/ /)	
环境条件:	
-20 $^{\circ}C$ ~+60 $^{\circ}C$	
10%RH~90%RH (40 $^{\circ}C$)	
80kPa~106kPa	
-40 $^{\circ}C$ ~+80 $^{\circ}C$	
功耗: $< 1W$	

Nanjing New Power Electric Co., Ltd.

→ 面板显示

○ PWR: ()

→ 注意事项

○

○

○

○

○

○ IEC/EN 60664-1 2