

NPFSR-K4F31MD

3X 1 WÄ 2 3 5
X3NO+1NC

h 3 y	24V AC/DC
3 y k T	0.85 ~ 1.1
r L	50Hz ~ 60Hz
Q i ä	2.2W/24V DC, 5.4VA/24V AC
3 3 L	50mA/24V DC
M i 3	
3 t	
2 Q	3NO+1NC
2 1 3	
2 a	AgSnO ₂ Tc 405390003 15: ~ 1.1
2 k	
2 R w 3 i	
T H	
Q H	
Ö H	
3 3 ~ H A Ä	
3 J k	
h N i 3 y	
h ~ ä p 3 y	
N i Ä y	
3 3 3 k 3 ~	
U	
y 3 i	
/ ... 3 i	
i 3 i	
t Ä □ y	
ü è □ y	
T ö y	
4 m u	

G 3 v Q		
ó í 3 i	PLd,	ISO 13849
G 3 i.	Cat.3,	ISO 13849
y n H	20 ,	ISO 13849
W z Ä ~ '	99%,	ISO 13849
W z и , Q H	162 ,	ISO 13849
H u t , Q	68,	ISO 13849
G 3 H Q ó 3 i	SIL2,	IEC 61508
φ " G 3 H Q ó 3 i	SIL CL2,	IEC 62061
. T Q y	1,	IEC 62061
G 3 , Q ' Q	,	IEC 62061
ð H и , Q H '	1.65×10 ⁻⁵ /PTI=20年,	IEC 61508
½ ñ H и , Q H '	1.91×10 ⁻¹⁰ 1/h,	IEC 62061
y B i.	0,	IEC 60204